



# DEGASi® PLUS SEMI-PREP


When working with higher flow rates, up to 6 ml/min, we strongly recommend DEGASi® SEMI-PREP equipped with 925 µl degassing chambers. These chambers can be used up to 10 ml/min but with a bit lower degassing efficiency.

*“manages higher flow rates  
up to 6–10 ml/min...”*

## PRODUCT FEATURES

- Ultra-high degassing efficiency
- Fits every system
- Long life expectancy: 5+ years continuous (24/7) running capacity
- Easy to prime
- Almost silent
- Closed loop vacuum control means constant vacuum (variable RPM)
- ZHCR® patented control eliminates baseline fluctuations
- Excellent chemical compatibility flow path
- Biocompatible flow path
- Continuous vacuum system monitoring to ensure optimal operational conditions are maintained
- Advanced error and leak checking functions
- CE & RoHS compliant

Part Number	Number of Channels	Internal Volume
0003-6351-L	1	925 µl
0003-6352-L	2	925 µl
0003-6353-L	3	925 µl
0003-6354-L	4	925 µl
0003-6355-L	5	925 µl
0003-6356-L	6	925 µl



## GENERAL SPECIFICATIONS

### Degassing Channel Tubing:

System AF™ (0.045" ID)

### Maximum Channel Pressure:

70 PSI

### Wetted Materials:

System AF™, PEEK, Glass-filled PTFE

### Liquid Connection:

1/4"-28 UNF threaded flat-bottom port

### Size (L x H x W):

245 x 111 x 59 mm

## POWER REQUIREMENTS USING SUPPLIED AC ADAPTER

24 V Power supply included.

Required input to power supply:

110-240 V 50/60 HZ

Wall Sockets: 4 supplied with AC Adapter, Interchangeable: North America, Japan, U.K., Continental Europe, Australia